




AerPOS
*15" Bezel Free Fan-less
POS Terminal*



AERPOS

		
Space Saving, Small Footprint and Upright Design Upright elongated design delivers a sophisticated look for high-end environments such as fashion apparel and hotel	Downward Facing I/O Connector Panel for Better Countertop Management Neatly conceals cabling under terminal for workspace	Ultra Slim Magnetic Stripe Reader Module MSR reader measures one centimeter in thickness when installed

Specifications

AP-3435	
Processor	: Intel® Atom™ D525, 1M L2 Cache 1.8Ghz
System Memory	: 1GB Standard, Maximum 4GB (1x204-pin DDR3)
Power Supply	: 90W (12V / 7.5A) External Power Supply
Storage Device	: 1 x 2.5" SATA HDD
Chipset	: Intel® GMA 3150
Speaker	: Internal Speaker 2W x 2
Construction	: Aluminum Die-casting + Plastic + Glass
Housing Color	: Black with Silver Trim or White with Silver Trim
Touch LCD Display	
Size / Resolution	: 15" TFT-LCD/ 1024 X 768
Brightness (Backlight Type) & Touch Screen	: 250 cd/m2 (CCFL); 5-Wire Resistive Touch
	: 350 cd/m2 (LED) with Tempered Glass; Projected Capacitive Touch

AerPOS
*15" Bezel Free Fan-less
POS Terminal*



Specifications

I/O Ports		
Serial Port	:	3 x External: COM1, COM2 (DB9), COM4 (RJ-45)
USB Port	:	5 x External (4 Rear + 1 Side)
Cash Drawer Port	:	1 x RJ11 (12V)
Printer Port	:	1 x Bi-directional Parallel port
Keyboard / Mouse	:	1 x PS/2
LAN Port	:	1 x RJ45 Giga LAN
Audio Port	:	1 x Line Out
VGA Port	:	1 x VGA
DC Output	:	1 x 12V DC Jack 2.5 mm
Optional I/O Board		
Type A	:	Serial Port: COM3 & COM5 (RJ - 45)
OS Supported		
Windows	:	Windows XP, POSReady 2009, Windows 7, POSReady 7
Linux	:	Per Request
Physical Dimension		
Dimensions (W x H x D)	:	367 x 352 x 223 mm
Environment		
EMI / Safety	:	CE, FCC Class A
Operating Temperature	:	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	:	-10°C ~ 55°C (14°F ~ 131°F)
Relative Humidity	:	10% ~ 90% (Non-condensing)

AerPOS

*15" Bezel Free Fan-less
POS Terminal*



Specifications

Optional Peripherals	
Magnetic Stripe Card Reader :	Integrated MCR Module (Single / Dual / Triple Track Selectable)
2nd Display :	Integrated 11.6" or 15" LCD Display (Touch Screen Optional)
Customer Display :	Integrated LCM / VFD Customer Display
Wireless Lan :	Integrated 802.11 b/g/n Wireless Module
Identification Devices :	RFID 13.56 MHz / Fingerprint Reader / i-Button