


AERPPC		
		
Easy installation of AerPPC onto a base	Display can be tilted various angles.	AerPPC is very versatile and offers many optional add-on devices

Specifications

AP-3435	
Processor	: Intel® Celeron® G540, 2,5Ghz / Intel® Core i5-330S, 3.0Ghz
System Memory	: 2GB Standard, Maximum 8GB (1x204-pin DDR3)
Power Supply	: 150W (12V / 12.5A) External Power Supply
Storage Device	: 2 x 2.5" SATA HDD or SSD (Operational RAID 1 Support)
Chipset	: Intel® H61
Construction	: Aluminum Die-casting + Plastic + Glass
Housing Color	: Black with Silver Trim
OS Supported	
Windows	: Windows XP, POSReady 2009, Windows 7, POSReady 7
Touch LCD Display	
Size / Resolution	: 17" TFT-LCD/ 1280 X 1024
Brightness (Backlight Type) & Touch Screen	: 250 cd/m2 (CCFL); 5-Wire Resistive Touch
	: 250 cd/m2 (LED) with Tempered Glass; Projected Capacitive Touch

AerPPC
*17" High Performance
Panel PC*



Specifications

I/O Ports		
Serial Port	:	3 x External: COM1, COM2 (DB9), COM4 (RJ-45)
USB Port	:	5 x External (4 Rear + 1 Side)
Cash Drawer Port	:	1 x RJ11 (12V)
Printer Port	:	1 x Bi-directional Parallel port
Keyboard / Mouse	:	1 x PS/2
LAN Port	:	1 x RJ45 Giga LAN
Expansion Slot	:	1 x Mini PCI-e (Internal)
Audio Port	:	1 x Line Out
VGA Port	:	1 x VGA
DC Input	:	1 x 12V DC
DC Output	:	1 x 12V DC Jack 2.5 mm
Physical Dimension		
Dimensions (W x H x D)	:	410 x 332 x 75 mm (Without Base); 410 x 364 x 250 mm (With Base)
Carton Dimensions (W x H x D)	:	510 x 450 x 230 mm (Without Base); 540 x 540 x 370 mm (With Base)
Weight	:	10kg (Net), 12kg (Gross)

AerPPC
*17" High Performance
Panel PC*



Specifications

Optional I/O Board		
Type A	:	Serial Port: COM A & COM B (RJ45) with RI / 5V / 12V Selectable; DC Output: 1 x 24V; 1 x Mic-in
Type B	:	Serial Port: COM A & COM B (RJ45) RI / 5V / 12V Selectable; Powered USB Port: 1 x 24V; 1 x Mic-in
Type C	:	Serial Port: COM A & COM B (RJ45) RI / 5V / 12V Selectable; Powered USB Port: 1 x 24V; 1 x Mic-in
Type E	:	Cash Drawer Port: 2 x 24V ; 1 x Mic-in
Type G	:	Powered USB Port: 3 x 12V
Type H	:	Powered USB Port: 2 x 12V, 1 x 24V