

## EagleEye EB-6086



### Specifications

Pick up Device	:	1/3" SONY CCD	
TV System	:	PAL	NTSC
Picture Elements	:	752Hx582V	752Hx582V
Scanning System	:	2:1 Interlace	
Horizontal Resolution	:	600 TVL	
Sensitivity	:	0 Lux at F1.2 (Infrared LED On)	
Synchronization		Internal	
Infrared Spectrum		, 850nm	
S/N Ratio		More than 48 dB, (AGC Off)	
Auto Gain Control (AGC)		Auto	
White Balance		Auto	
Electronic Shutter		PAL:1/501/10000S	NTSC:1/601/10000S
Back Light Compensation		Auto	
Infrared LED		30pcs of $\phi$ 5mm	
Infrared LED Range		25m	
Video Output		1 Vp-p, 75 $\Omega$ composite , BNC x1	
Audio Output		N/A	
Mirror		N/A	
Gamma Ratio		0.45	
Auto-iris Lens Control		N/A	

## EagleEye EB-6086



### Specifications

Lens	:	3.6mm,6mm,8mm Lens optional
Exterior Focus Adjustment	:	N/A
Lens Mount	:	M12XP0.5mm Thread
Pan Adjusting		N/A
Tilt Adjusting		N/A
Power Supply		12V DC $\pm$ 10%, $\varnothing$ 2.0mm DC Jack x1
Dimensions ( $\varnothing$ X H)		L152xW120xH75mm
Net Weight		350 g
Weatherproof/Water Proof		Waterproof
Operating Temperature		-20°C to +50°C

## EagleEye EB-7086



### Specifications

Pick up Device	:	1/3" SONY CCD	
TV System	:	PAL	PAL
Picture Elements	:	960(H)×582(V)	960(H)×582(V)
Scanning System	:	2:1 Interlace	
Horizontal Resolution	:	700 TVL	
Sensitivity	:	0 Lux at F1.2 (Infrared LED On)	
Synchronization		Internal	
Infrared Spectrum		, 850nm	
S/N Ratio		More than 48 dB, (AGC Off)	
Auto Gain Control (AGC)		Auto	
White Balance		Auto	
Electronic Shutter		PAL:1/501/10000S	NTSC:1/601/10000S
Back Light Compensation		Auto	
Infrared LED		30pcs of $\phi$ 5mm	
Infrared LED Range		25m	
Video Output		1 Vp-p, 75 $\Omega$ composite , BNC x1	
Audio Output		N/A	
Mirror		N/A	
Gamma Ratio		0.45	
Auto-iris Lens Control		N/A	

## EagleEye EB-7086



### Specifications

Lens	:	3.6mm,6mm,8mm Lens optional
Exterior Focus Adjustment	:	N/A
Lens Mount	:	M12XP0.5mm Thread
Pan Adjusting		N/A
Tilt Adjusting		N/A
Power Supply		12V DC $\pm$ 10%, $\varnothing$ 2.0mm DC Jack x1
Dimensions ( $\varnothing$ X H)		L152xW120xH75mm
Net Weight		350 g
Weatherproof/Water Proof		Waterproof
Operating Temperature		-20°C to +50°C