

## EagleEye ER-7090 V



### Specifications

Pick up Device	:	1/3" SONY CCD	
TV System	:	PAL	PAL
Picture Elements	:	752Hx582V	768Hx494V
Scanning System	:	2:1 Interlace	
Horizontal Resolution	:	700 TVL	
Sensitivity	:	0 Lux at F1.2 (Infrared LED On)	
Synchronization		Internal	
Infrared Spectrum		, 850nm	
S/N Ratio		More than 48 dB, (AGC Off)	
Auto Gain Control (AGC)		Auto	
White Balance		Auto	
Electronic Shutter		PAL:1/501/10000S	NTSC:1/601/10000S
Back Light Compensation		Auto	
Infrared LED		42pcs of 5mm IR LED	
Infrared LED Range		50m	
Video Output		1 Vp-p, 75Ωcomposite , BNC x1	
Audio Output		N/A	
Mirror		N/A	
Gamma Ratio		0.45	
Auto-iris Lens Control		N/A	

## EagleEye ER-7090 V



### Specifications

Lens	:	4-9mm varifocal Lens
Exterior Focus Adjustment	:	N/A
Lens Mount	:	M12XP0.5mm Thread
Pan Adjusting		N/A
Tilt Adjusting		N/A
Power Supply		12V DC $\pm$ 10%, $\varnothing$ 2.0mm DC Jack x1
Dimensions ( $\varnothing$ X H)		L245XW83XH76mm
Net Weight		950g
Weatherproof/Water Proof		Waterproof
Operating Temperature		-20°C to +50°C